



# Standard Passthrough Dishwashers



Introducing the new Standard Range Passthrough from DC, specifically designed to meet the rigorous demands of all UK catering outlets.

Standard Range

SD900



- Fast
- Powerful
- Energy Efficient
- Economical



## Performance

**Fast, powerful wash cycle**  
for maximum productivity and deep cleaning

**Heavy duty heater elements**  
faster start up and improved heat recovery times

**Hood auto-start**  
increases speed and productivity and reduces user intervention

**Rinse thermo-lock**  
delivers perfect rinse temperatures time after time

**Increased usable height**  
accommodates larger items such as trays, pots and utensils

## Energy and Cost Savings

**Low volume wash tank**  
reduces water consumption and chemical costs

**Reduced electrical costs**  
low water usage requires less energy to heat the machine

**Improved rinse arms**  
increases initial response by 30% and rotation speed by 20%

## Operation

**Intuitive, simple controls**  
reduces user error and staff training

**Counter balanced hood**  
makes loading and unloading easier for the operator

**Chemical auto-dosing (optional)**  
eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**  
ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**  
softens water without the need for an external unit

'Welcome to a cleaner world'

## Standard Range Passthrough Specifications

18



	SD900
Cycle time	120/180 sec
Baskets (x3)	500 x 500 mm
Height	1475 mm
Height - hood raised	1930 mm
Width	655 mm
Width inc' handle	725 mm
Depth	770 mm
Usable wash height	400 mm
Drain height	470 mm
Drain diameter Ø	32 mm
Wash tank	22 lts
Boiler	5 lts
Water usage	2.4 lts p/c
Wash element	3.0 kW
Boiler element	6.0 kW
Total load	6.75 kW
Amps required	30 Amps*
Detergent dosing	Yes
Rinse aid dosing	Yes
Water connection	3/4 BSP
Required water pressure	2-4 bar
Drain pump	Optional
Internal softener**	Optional
Break tank (WRAS)	Optional



**Where water hardness exceeds 100ppm a water softener is required.**

\*Can be configured to run on either 20A or 3Ph+N upon request.

\*\*Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products Ltd.

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcproducts.co.uk

