



# Economy Glasswashers



Introducing the new Economy Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



- **Fast**
- **Economical**
- **Robust**
- **Hygienic**



## Performance

**Fast two minute wash cycle**  
ensures maximum productivity

**New innovative wash pump**  
increases wash pressure improving results

**Rinse thermo-lock**  
delivers perfect rinse temperatures time after time

## Energy and Cost Savings

**New innovative wash pump**  
saves 180W per hour

**Reduced water consumption**  
produces the optimum balance between water usage and hygiene

**Improved rinse arms**  
increases initial response by 30% and rotation speed by 20%

## Operation

**Intuitive, simple controls**  
reduces user error and staff training

**EasyClean filters**  
maintenance friendly filters protect critical components

**Chemical auto-dosing**  
eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**  
ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**  
softens water without the need for an external unit

*Welcome to a Cleaner World*

## Economy Range Glasswasher Specifications



	EG35 / EGP35	EG40 / EGP40
Cycle time	120 sec	120 sec
Baskets (x2)	350 x 350 mm	400 x 400 mm
Height	590 mm/645 mm	640 mm/690 mm
Width	415 mm	465 mm
Depth	465 mm	510 mm
Depth with door open	705 mm	785 mm
Usable wash height	205 mm/245 mm	240 mm/280 mm
Drain height	120 mm	120 mm
Drain Ø	25 mm	25 mm
Wash tank	11 L	14 L
Boiler	2.8 L	2.8 L
Water usage	2.4 L p/c	2.4 L p/c
Wash element	1.6 kW	1.6 kW
Boiler element	2.8 kW	2.8 kW
Total load	3 kW	3 kW
Amps required	13 Amps	13 Amps
Detergent dosing	Yes	Yes
Rinse aid dosing	Yes	Yes
Water connection	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar
Required water flow rate	10 L p/min	10 L p/min
Drain pump	Optional	Optional
Internal softener*	Optional	Optional

### Where water hardness exceeds 100ppm a water softener is required.

\*Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



**DC Products**

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk [www.dcprouducts.co.uk](http://www.dcprouducts.co.uk)

